



635nm 50mW PM Fiber Coupled Laser Diode with Coaxial Package | Red Laser Diode
635nm~638nm 50mW Coaxial Pigtailed LD with Polarization Maintaining Fiber (SM Fiber)
 WSLP-635-050m-PM Wavespectrum Laser Group www.wavespectrum-laser.com

635nm Pigtailed Diode Laser		50mW/PM Fiber		en.wavespectrum-laser.com.cn	
PARAMETER	SYMBOL	VALUE		UNIT	
Reverse Voltage	V_r	2.0		V	
Operating Temperature	T_{op}	-10~+60		°C	
Storage Temperature	T_{stg}	-40~+85		°C	
Lead soldering temperature (10 sec.)	T_{is}	260		°C	
Features: <ul style="list-style-type: none"> ● 635nm ● PM Fiber ● High Reliability ● High Polarization Extinction Ratio Applications: <ul style="list-style-type: none"> ● Biological Instruments ● Analytical Equipment ● Others 					
Specifications	WSLP-635-050m-PM				
	Min	Type	Max		
Center Wavelength@25°C	630nm	638nm	645nm		
Recommended work Temperature	25°C				
Output Power	----	50mW	----		
Fiber Type	Polarization Maintaining Fiber				
Fiber Core	4um				
Polarization Extinction Ratio	13dB	15dB	----		
Monitor Current	----	----	----		
Fiber Connector	FC/APC				
Fiber Length	----	80cm	100cm		
Threshold Current	----	65mA	90mA		
Operating Current	----	210mA	230mA		
Operating Voltage	----	2.8V	3.3V		
Package Style	Coaxial or B82				
High Polarization Extinction Ratio (PER) Version Laser Module is also available, please contact us.					



Coaxial Package View: (Part Number: WSLP-635-050m-PM)

B82 Package View: (Part Number: WSLP-635-050m-PM-B)

PIN Bottom View:


1	LD(+)
2	LD(-)



Electrically shorten LD module and store in non-extreme conditions.
Suggest using the constant current power supply.

