


650nm~660nm 20mW~30mW SM Fiber Coupled Laser Diode with 4um SMF
650nm 20mW Coaxial Pigtailed LD with Single Mode Fiber | Red Diode Laser Module

WSLP-650-020m-4




Wavespectrum Laser Group

www.wavespectrum-laser.com

650nm Pigtailed Diode Laser		20mW/SM Fiber		en.wavespectrum-laser.com.cn	
PARAMETER	SYMBOL	VALUE	UNIT		
Reverse Voltage	V_r	2.0	V		
Operating Temperature	T_{op}	-10~+60	°C		
Storage Temperature	T_{stg}	-40~+85	°C		
Lead soldering temperature (10 sec.)	T_{is}	260	°C		
Features: <ul style="list-style-type: none"> 650nm Single Mode Fiber Coaxial or B82 Package 					
Applications: <ul style="list-style-type: none"> Medical Laser Treatment Other 					
Specifications	WSLP-650-020m-4				
	Min	Type	Max		
Center Wavelength@25°C	±5nm	658nm	±10nm		
Spectral Width (FWHM)	----	2.0nm	----		
Output Power	----	20mW	----		
Fiber Type	Single Mode Fiber				
Fiber Core	4um				
Recommend Operating Temperature	25°C				
Fiber Connector	FC/SC/SMA905				
Fiber Length	----	80cm	100cm		
Threshold Current	----	45mA	65mA		
Operating Current	----	140mA	160mA		
Operating Voltage	----	2.6V	3.2V		
Package Style	Coaxial or B82				



Coaxial Package View: (Part Number: WSLP-650-020m-4)

B82 Package View: (Part Number: WSLP-650-020m-4-B)

PIN Bottom View:


1	LD(+)
2	LD(-)
3	NC



Electrically shorten LD module and store in non-extreme conditions.
Suggest using the constant current power supply.

