






670nm 3mW PM Fiber Coupled Laser Diode with Coaxial Package | Red Laser Diode
670nm~675nm 3mW Coaxial Pigtailed LD with Polarization Maintaining Fiber (SM Fiber)
 WSLP-670-003m-PM-PD Wavespectrum Laser Group www.wavespectrum-laser.com

670nm Pigtailed Diode Laser		3mW/PM Fiber		en.wavespectrum-laser.com.cn	
PARAMETER	SYMBOL	VALUE	UNIT		
Reverse Voltage	V_r	2.0	V		
Operating Temperature	T_{op}	-10~+60	°C		
Storage Temperature	T_{stg}	-40~+85	°C		
Lead soldering temperature (10 sec.)	T_{is}	260	°C		
Features: <ul style="list-style-type: none"> 670nm PM Fiber High Reliability High Polarization Extinction Ratio Applications: <ul style="list-style-type: none"> Biological Instruments Analytical Equipment Others 					
Specifications	WSLP-670-003m-PM-PD				
	Min	Type	Max		
Center Wavelength@25°C	±5nm	670nm	±10nm		
Recommended work Temperature	25°C				
Output Power	----	3mW	----		
Fiber Type	Polarization Maintaining Fiber				
Fiber Core	4um				
Polarization Extinction Ratio	13dB	15dB	----		
Monitor Current	----	0.5mA	----		
Fiber Connector	FC/APC				
Fiber Length	----	80cm	100cm		
Threshold Current (Typ.)	----	20mA	30mA		
Operating Current (Typ.)	----	35mA	40mA		
Operating Voltage	----	2.3V	2.8V		
Package Style	Coaxial or B82				
High Polarization Extinction Ratio (PER) Version Laser Module is also available, please contact us.					



Coaxial Package View: (Part Number: WSLP-670-003m-PM-PD)

B82 Package View: (Part Number: WSLP-670-003m-PM-B-PD)

PIN Bottom View:


1	LD(-)
2	LD(+)&PD(-)
3	PD(+)



Electrically shorten LD module and store in non-extreme conditions.
Suggest using the constant current power supply.

