

RGB White Laser|638nm+520nm+450nm|White Light|Fiber Coupled Laser Diode|Pigtailed Laser Module|Pigtal LD | PM Fiber PMF
 3um-4um SM Fiber| Single Mode Fiber| SMF|TEC TE Cooler| Triplex Diode Laser|405nm-445nm-450nm-455nm-460nm-488nm|Blue
 633nm-635nm-638nm-650nm-658nm-660nm-670nm-680nm-685nm-690nm|Red|505nm-510nm-515nm-520nm-525nm-532nm|Green
 Triplex-WSLX-445/020m-520/020m-635/020m-4-H-T Wavespectrum Laser Group en.wavespectrum-laser.com.cn

Triplex - RGB Fiber Coupled White Laser Diode

Features:

- RGB (638nm+520nm+450nm) Solution
- 3um Single Mode Fiber
- >20mW Power for Each Wavelength
- Perfect White Laser Output
- Built-in TE Cooler



Applications:

- Endoscopy
- Aiming Beam
- Bioscience
- Illumination

WAVESPECTRUM can offer Triplex-RGB Fiber Coupled White Laser Module. We couple the Red (638nm), Green (520nm) and Blue (450nm) Laser into one piece of fiber to get the perfect white Laser. The Fiber Type can be Single Mode Fiber (SMF) , Multi-Mode Fiber (MMF) and Polarization Maintaining Fiber (PMF). The fiber core can be 3um, 9um, 50um, 105um, etc. The output power can upto 200mW. By controlling the ratio of RGB Laser, we can get the perfect white laser. Meanwhile, by adjusting the ratio, various colors of laser also can be obtained.

Meanwhile, various of RGB Wavelength Combinations are available, such as Red Laser (635nm, 650nm, 660nm, 670nm, 685nm) +Green Laser (505nm, 515nm, 520nm)+Blue Laser (405nm, 450nm, 460nm).

WAVESPECTRUM can offer various wavelengths listed as below: 375nm, 405nm, 445nm/450nm, 465nm, 488nm, 505nm/510nm, 515nm/520nm/525nm, 633nm, 635nm/638nm/640nm/642nm, 650nm/658nm/660nm, 670nm, 685nm/690nm, 705nm, 730nm, 755nm/760nm/770nm, 780nm/785nm, 795nm, 800nm/808nm/810nm, 820nm/830nm, 840nm/850nm/860nm, 880nm, 905nm, 915nm, 940nm, 976nm/980nm, 1060nm/1064nm, 1210nm, 1270nm, 1280nm, 1290nm, 1310nm, 1330nm, 1350nm, 1370nm, 1390nm, 1410nm, 1430nm, 1450nm, 1470nm, 1490nm, 1510nm, 1530nm, 1550nm, 1570nm, 1590nm, 1610nm, 1625nm, 1650nm, 1720nm, 1900nm, 1920nm.

WAVESPECTRUM can provide a variety of laser products: single mode laser diode, multi-mode laser diode, single mode fiber coupled laser modules, polarization maintaining fiber coupled laser modules, multi-mode pigtailed laser modules, fiber detachable laser modules, RGB white fiber coupled laser module, medical laser module, turnkey fiber coupled laser system, etc. The main packages for the lasers can be: TO18 | TO5 | C-mount | TO3 | E-mount | H-mount | COS | 2-pin | 4-pin | 9-pin | 14-pin.

WAVESPECTRUM - welcome to to inquire any time!

Pls visit our Website for more info.: <http://www.wavespectrum-laser.com.cn/index.html>

MORE CHOICES, MORE IDEAS



Laser Diode	Fiber Coupled Laser Module	Fiber Receptacle LD	Laser System	RGB Pigtailed White Laser	Medical Laser Module
375nm	405nm	445nm	465nm	488nm	505nm
685nm	760nm	785nm	790nm	808nm	830nm
1064nm	1210nm	1270nm	1280nm	1290nm	1310nm
1470nm	1490nm	1510nm	1530nm	1550nm	1570nm
				1590nm	1610nm
				1625nm	1650nm
				1720nm	1720nm
				1900nm	1900nm
				1920nm	1920nm

WAVESPECTRUM LASER GROUP LIMITED

Email: sales@wavespectrum-laser.com.cn

Tel.: +86 22 8793 1118


Web.: <http://en.wavespectrum-laser.com.cn>



RGB White Laser|638nm+520nm+450nm|White Light|Fiber Coupled Laser Diode|Pigtailed Laser Module|Pigtail LD | PM Fiber PMF 3um-4um SM Fiber| Single Mode Fiber| SMF|TEC TE Cooler| Triplex Diode Laser|405nm-445nm-450nm-455nm-460nm-488nm|Blue 633nm-635nm-638nm-650nm-658nm-660nm-670nm-680nm-685nm-690nm|Red|505nm-510nm-515nm-520nm-525nm-532nm|Green Triplex-WSLX-445/020m-520/020m-635/020m-4-H-T Wavespectrum Laser Group en.wavespectrum-laser.com.cn


Triplex - RGB Fiber Coupled White Laser Diode

Part Number		Triplex-WSLX-445/020m-520/020m-635/020m-4-H-T		
PARAMETER		SYMBOL	VALUE	UNIT OF MEASURE
Reverse Voltage		V_r	2.0	V
Operating Temperature		T_{op}	-10~+50	°C
Storage Temperature		T_{stg}	-40~+80	°C
Lead Soldering Temperature (10 sec.)		T_{ls}	260	°C
Typical Specification (@25°C)		Wavelength-1	Wavelength-2	Wavelength-3
Optical Specifications	Center Wavelength	450nm±10nm	520nm±10nm	638nm±10nm
	Output Power (CW)	20mW	20mW	20mW
	Spectral Width(FWHM)	2nm	2nm	2nm
	Wavelength Temp. Coefficient	0.05nm/°C	0.05nm/°C	0.2nm/°C
	M ² Value	<1.3	<1.3	<1.3
	Beam Type	Gaussian Beam		
	Laser Type	FP		
Fiber Specifications	Fiber Core	3um		
	N.A.	0.12		
	Fiber Type	Single Mode Fiber		
	Fiber Length	>80cm		
	Fiber Connector	FC/SMA905/SC/ST		
Electrical Specifications	Threshold Current	25mA	60mA	60mA
	Operating Current (Typ.)	140mA	240mA	200mA
	Operating Voltage	6.5V	7.5V	3.0V
TE Cooler Specifications	TEC Current (Max.)	3.5A		
	TEC Voltage (Max.)	7.0V		
Thermistor	Thermistor (@25°C)	10K		
Other Specifications	Package	HHL-01		
	Recommended Operating Temp.	25°C		






Laser Beam with 3um SM Fiber:




Product Package View:

HHL-01 Package View:



Pin Bottom View: HHL-01



PIN	FUNCTION	PIN	FUNCTION
1 (Blue)	445nm LD(+)	6 (Black)	635nm LD(-)
2 (Green)	445nm LD(-)	7 (Orange)	Thermistor
3 (White)	520nm LD(+)	8 (Purple)	Thermistor
4 (Yellow)	520nm LD(-)	9 (Brown)	TEC(+)
5 (Red)	635nm LD(+)	10 (Gray)	TEC(-)

