

1064nm MM Fiber Coupled LD | 1064nm MMF Pigtailed Laser Diode | Laser Module | TEC | Coaxial 14PIN BTF 9PIN HHL | PD  
 1055nm~1060nm~1064nm | 4W | 50um 60um 105um 200um 400um Multi-mode Fiber | 2PIN 4PIN Package | Pigtail LD | Photodiode  
 WSLX-1064-004-M-H2 Wavespectrum Laser Group en.wavespectrum-laser.com.cn

## 1064nm 4W Multi-mode Fiber Coupled Laser Diode

### Features:

- 1064nm
- 105um Multi-Mode Fiber
- 2-Pin Package
- Photodiode Optional
- TE Cooler Optional

### Applications:

- Medical Laser Treatment
- Biological Laser
- Others



WAVESPECTRUM can offer high stability fiber coupled laser module. The fiber types can be single-mode fiber (SMF), polarization maintaining fiber (PMF) and multimode fiber (MMF). We choose the world's top level laser chips in making the lasers to ensure the high quality. And the lasers will undergo severe restricted aging and testing before sending to the customer. At present, we can offer the pigtailed laser products with the wavelength range of 375nm ~ 1920nm, and the output power range is from 1mW to 50W. We adopt the unique technical scheme to makes the laser and the lasers are of high stability and low noise. For single-mode fiber (SMF) and polarization maintaining fiber (PMF) coupling laser, the light spot is single transverse mode Gaussian beam. And the polarization extinction ratio can reach greater than 20dB (PER) as per customer's requirements.

WAVESPECTRUM can offer various wavelengths listed as below: 375nm, 405nm, 445nm/450nm, 465nm, 488nm, 505nm/510nm, 515nm/520nm/525nm, 633nm, 635nm/638nm/640nm/642nm, 650nm/658nm/660nm, 670nm, 685nm/690nm, 705nm, 730nm, 755nm/760nm/770nm, 780nm/785nm, 795nm, 800nm/808nm/810nm, 820nm/830nm, 840nm/850nm/860nm, 880nm, 905nm, 915nm, 940nm, 976nm/980nm, 1060nm/1064nm, 1210nm, 1270nm, 1280nm, 1290nm, 1310nm, 1330nm, 1350nm, 1370nm, 1390nm, 1410nm, 1430nm, 1450nm, 1470nm, 1490nm, 1510nm, 1530nm, 1550nm, 1570nm, 1590nm, 1610nm, 1625nm, 1650nm, 1720nm, 1900nm, 1920nm.


WAVESPECTRUM can provide a variety of laser products: single mode laser diode, multimode laser diode, single mode fiber coupling laser modules, polarization maintaining fiber coupled laser modules, multi-mode pigtailed laser modules, fiber detachable laser module, RGB white fiber coupled laser module, medical laser module, turnkey fiber coupled laser system, etc. The main packages for the lasers can be: TO18 | TO5 | C-mount | TO3 | E-mount | H-mount | COS | 2-pin | 4-pin | 9-pin | 14-pin.

WAVESPECTRUM - welcome to to inquiry any time!  
 Pls visit our Website for more info.: <http://www.wavespectrum-laser.com.cn/index.html>

### MORE CHOICES, MORE IDEAS

Laser Diode	Fiber Coupled Laser Module	Fiber Receptacle LD	Laser System	RGB Pigtailed White Laser	Medical Laser Module
375nm	405nm	445nm	465nm	488nm	505nm
685nm	760nm	785nm	790nm	808nm	830nm
1064nm	1210nm	1270nm	1280nm	1290nm	1310nm
1470nm	1490nm	1510nm	1530nm	1550nm	1570nm
<b>WAVESPECTRUM LASER GROUP LIMITED</b>					
Email: <a href="mailto:sales@wavespectrum-laser.com.cn">sales@wavespectrum-laser.com.cn</a>					
Tel.: +86 22 8793 1118					
Web.: <a href="http://en.wavespectrum-laser.com.cn">http://en.wavespectrum-laser.com.cn</a>					






1064nm MM Fiber Coupled LD | 1064nm MMF Pigtailed Laser Diode | Laser Module | TEC | Coaxial 14PIN BTF 9PIN HHL | PD  
 1055nm~1060nm~1064nm | 4W | 50um 60um 105um 200um Multi-mode Fiber | 2PIN 4PIN Package | Pigtail LD | Photodiode  
 WSLX-1064-004-M-H2 Wavespectrum Laser Group en.wavespectrum-laser.com.cn

## 1064nm 4W Multi-mode Fiber Coupled Laser Diode

Part Number		WSLX-1064-004-M-H2		
PARAMETER	SYMBOL	VALUE	UNIT OF MEASURE	
Reverse Voltage	V <sub>r</sub>	2.0	V	
Operating Temperature	T <sub>op</sub>	+10~+30	°C	
Storage Temperature	T <sub>stg</sub>	-20~+80	°C	
Lead Soldering Temperature (10 sec.)	T <sub>is</sub>	260	°C	
Typical Specification (@25°C)	Min.	Typical Value		Max.
Optical Specifications	Center Wavelength	1064nm +/- 20nm		
	Output Power	----	4W	----
	Spectral Width(FWHM)	----	4.0nm	----
	Wavelength Temp. Coefficient	0.35nm/°C		
	Laser Type	FP		
Fiber Specifications	Fiber Core	105um		
	N.A.	0.22		
	Fiber Type	Multi-mode Fiber		
	Fiber Length	>80cm		
	Fiber Connector	FC/SMA905/SC/ST		
Electrical Specifications	Threshold Current	----	0.5A	1.0A
	Operating Current	----	6.5A	7.0A
	Operating Voltage	----	1.6V	2.0V
Photodiode Specifications	Photodiode	Without		
	PD Current	----	----	----
	PD Reverse Voltage (Max.)	----		
TE Cooler Specifications	TEC Current (Max.)	----		
	TEC Voltage (Max.)	----		
Thermistor	Thermistor (@25°C)	----		
Other Specifications	Package	2-Pin		
	Recommended Operating Temp.	25°C		





1064nm MM Fiber Coupled LD | 1064nm MMF Pigtailed Laser Diode | Laser Module | TEC | Coaxial 14PIN BTF 9PIN HHL | PD  
1055nm~1060nm~1064nm | 4W | 50um 60um 105um 200um 400um Multi-mode Fiber | 2PIN 4PIN Package | Pigtail LD | Photodiode  
WSLX-1064-004-M-H2 Wavespectrum Laser Group en.wavespectrum-laser.com.cn

## 1064nm 4W Multi-mode Fiber Coupled Laser Diode

### Product Package View:

#### 2-Pin Package View:

(Part Number: WSLX-1064-004-M-H2)

